



AD TOWERGEN

DATA SHEET

AD4-320L

AD4-320L FAST



*Image for illustration purposes only

LED

LUMEN

ILLUMINATED AREA

4x320W LED

180.000 lm

5000 sqm (20 lux)
9300 sqm (01 lux)

Fluid Safety Ltd
Unit 3b Arbour Court
Arbour Lane
Knowsley Industrial Park
L33 7XE



TEL: 0151 459 9449

TECHNICAL SPECIFICATIONS

Rated Frequency	50 Hz	
Voltage	230V	
Operating Temperature	-20/+40°	
Sound Level	61 dBA	
Control Unit	ComAp LTC80 / DeepSea L401 MKII	
Auxiliary Power	1,5 kVA	
Engine		
Model	Yanmar 2TNV70	
Speed	1500 rpm	
Coolant	Liquid	
Cylinders	2	
Emissions	Stage V	
Alternator		
Model	Linz Alumen	
Output Power	3.5 kVA	
Consumption		
Fuel Consumption	0,55 l/h	
Tank	100 l	
Fuel	Diesel	
Running Time	200 h	
Galvanised Mast Features		
Height	8.5 m	
Mast	Hydraulic	
Rotation	355°	
Wind Speed Resistance	110 km/h	
Canopy & Trailer	AD4-320L	AD4-320L FAST
Trailer	Site-tow Trailer	Tow Trailer EU Approved
Tyres	155/80/R13	185/70/R13
Collection Tank Base	110%	110%
Stabilisers	3	4 + 1 (wheel)
Canopy	Powder Coating Paint	Powder Coating Paint
Shipment Data		
Dimension	220 x 147 x 245 cm	
Weight	855 kg	
Truck	11 units	
Container 40"	11 units	
Optional		
Optional included as standard	Grid-engine Selector	
	Dusk to dawn sensor with Autostart	
	Trolley Safety System	
	Battery Isolator	
	Oil Extraction Pump	